



Revision Number: 007.1

Issue date: 01/27/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	TURCO ALUMIPREP 33	IDH number:	594416
Product type:	Cleaner	Region:	United States
Company address:		Contact information:	
Henkel Corporation		Telephone: 248.583.9300	
32100 Stephenson Highway		For Chemical Emergency: Call CHEMTREC at 800.424.9300	
Madison Heights, MI 48071		Internet: www.henkelna.com	

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	Liquid	HEALTH:	*3
Color:	Colorless	FLAMMABILITY:	2
Odor:	Solvent	PHYSICAL HAZARD:	0
		Personal Protection:	See MSDS Section 8

DANGER -- CORROSIVE!: **COMBUSTIBLE!**
CAUSES EYE, SKIN, DIGESTIVE TRACT, AND RESPIRATORY TRACT BURNS.
MAY BE HARMFUL IF SWALLOWED, ABSORBED THROUGH SKIN OR INHALED.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:	Mists, vapors or liquid may cause severe irritation or burns. Inhalation of mists or vapors may produce upper airway edema, wheezing, pulmonary edema, pneumonitis and respiratory failure.
Skin contact:	Corrosive to the skin. Contact with the skin or mucous membranes may cause severe irritation and burns. Following skin exposure to this product, the sensation of irritation or pain may be delayed. A component in this product may be harmful or fatal if absorbed through the skin.
Eye contact:	This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.
Ingestion:	This product may produce corrosive damage to the gastrointestinal tract if it is swallowed. May cause dizziness, incoordination, headache, nausea, and vomiting. Product contains a glycol ether which caused blood disorders in rabbits.

Existing conditions aggravated by exposure: Eye, skin and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Phosphoric acid	7664-38-2	10 - 30
2-Butoxyethanol	111-76-2	10 - 30
Surfactant	Proprietary	1 - 5
Potassium phosphate	Proprietary	1 - 5
Hydrogen fluoride	7664-39-3	0.1 - 1

4. FIRST AID MEASURES

Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.
Skin contact:	Remove contaminated clothing and footwear. For skin contact, flush with large amounts of water. Seek immediate medical attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting. Give one to two glasses of water or milk. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Notes to physician:	Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Flash point:	62.8 °C (145.04 °F) Tagliabue closed cup
Autoignition temperature:	Not applicable
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide. Use media appropriate for surrounding material.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	Fire and explosion hazards are moderate when this product is exposed to heat or flame. Vapors are heavier than air and may travel along floor to an ignition source.
Hazardous combustion products:	Irritating and toxic gases or fumes may be released during a fire.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not inhale vapors and fumes. Keep away from heat, spark and flame. For industrial use only.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty containers. Manufacturer recommends storing above 4.4 °C (40 °F). Thaw and mix thoroughly if frozen. Do not store above 100 °F (37.7 °C).

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Phosphoric acid	1 mg/m ³ TWA 3 mg/m ³ STEL	1 mg/m ³ TWA	None	None
2-Butoxyethanol	20 ppm TWA	(SKIN) 50 ppm (240 mg/m ³) TWA	None	None
Surfactant	None	None	None	None
Potassium phosphate	None	None	None	None
Hydrogen fluoride	(SKIN) (as F) 0.5 ppm TWA (as F) 2 ppm Ceiling (as F)	3 ppm TWA	None	None

Engineering controls: Use general ventilation and use local exhaust, where possible, in confined or enclosed spaces.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended. Gloves should be tested to determine suitability for prolonged contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Colorless
Odor:	Solvent
Odor threshold:	Not available
pH:	< 2
Vapor pressure:	Not determined
Boiling point/range:	> 200 °F (> 93.3 °C)
Melting point/ range:	Not available
Specific gravity:	1.12 - 1.16 at 15.6 °C (60.08 °F)
Vapor density:	Not determined
Flash point:	62.8 °C (145.04 °F) Tagliabue closed cup
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Evaporation rate:	Not available
Solubility in water:	Complete
Partition coefficient (n-octanol/water):	Not determined
VOC content:	14 % (by weight) (estimated)

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. May liberate hydrogen fluoride.
Incompatible materials:	This product may react with strong oxidizing agents.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Phosphoric acid	No	No	No
2-Butoxyethanol	No	No	No
Surfactant	No	No	No
Potassium phosphate	No	No	No
Hydrogen fluoride	No	No	No

Hazardous components	Health Effects/Target Organs
Phosphoric acid	Irritant, Corrosive
2-Butoxyethanol	Blood, Central nervous system, Irritant, Kidney, Liver
Surfactant	Irritant
Potassium phosphate	Gastrointestinal tract, Irritant, Metabolic
Hydrogen fluoride	Allergen, Blood, Bone Marrow, Cardiac, Central nervous system, Corrosive, Irritant, Kidney, Liver, Lung, Muscle, Nervous System, Respiratory, Teeth

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number:	This product, if discarded directly, would be a characteristic RCRA corrosive waste (D002). This product contains a component or components identified as hazardous under 40 CFR 261.24. U134: Hydrogen fluoride

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Corrosive liquid, acidic, inorganic, n.o.s. (Phosphoric acid, Hydrofluoric acid)
Hazard class or division:	8
Identification number:	UN 3264
Packing group:	II
DOT Reportable quantity:	Hydrofluoric acid, Phosphoric acid

International Air Transportation (ICAO/IATA)

Proper shipping name:	Corrosive liquid, acidic, inorganic, n.o.s. (Phosphoric acid, Hydrofluoric acid)
Hazard class or division:	8
Identification number:	UN 3264
Packing group:	II

Water Transportation (IMO/MDG)

Proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, Hydrofluoric acid)
Hazard class or division: 8
Identification number: UN 3264
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 2-Butoxyethanol (CAS# 111-76-2).
CERCLA Reportable quantity: Phosphoric acid (CAS# 7664-38-2) 5,000 lbs. (2,270 kg)
Hydrogen fluoride (CAS# 7664-39-3) 100 lbs. (45.4 kg)
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
WHMIS hazard class: B.3, D.1.B, D.2.B, E

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: John DiCerbo, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.